HardieReveal2.0™ Panel System

Project Name:			
Project Address:			
Start Date:		3	
Project Manager or Head Install Contact on Site:			
Number of floors and building height: (Max building height of 75 ft. for HardieReveal panel systems)			
		Please check one:	I I
Furring Type: Metal or Wood		☐ Single Family	Please check one:
GC/Installer Company Name:	Phone:	■ Multi-Family	■ New Construction
JH Rep:		☐ Commercial	☐ R&R

					Total
	SKU	Description	Qty	Unit	Units
^	☐ 617973 (HZ5 full pallet)		40	full pallet	
	☐ 6000277 (HZ5 sub pallet)	HARDIEREVEAL2.0™ PANEL	10	sub pallet	
	☐ 217973 (HZ10 full pallet)	Thickness 7/16 in., Width 47.5 in., Length 95.5 in.	40	full pallet	
	☐ 9000277 (HZ10 sub pallet)		10	sub pallet	
	Prime 9000318	HARDIEREVEAL2.0 OS CORNER TRIM Length: 8 ft.	15	Вох	
	Prime 9000319	HARDIEREVEAL2.0 HORIZONTAL TRIM Length: 8 ft.	30	Вох	
	Prime 9000320	HARDIEREVEAL2.0 VERTICAL TRIM Length: 8 ft.	30	Вох	
	Prime 9000321	HARDIEREVEAL2.0 DRAINAGE FLASHING Length: 8 ft.	30	Вох	
	Prime 9000373	HARDIEREVEAL2.0 HORIZONTAL EDGE TRIM Length: 8 ft.	10	Вох	
THE STATE OF	Prime 9000372	HARDIEREVEAL2.0 PVC VENT STRIP Length: 8 ft.	50	Вох	
	Prime 9000374	HARDIEREVEAL2.0 F TRIM VERTICAL Length: 8 ft.	15	Вох	

HardieReveal2.0™ Panel System

Send quote to multi.family@jameshardie.com or fax to 866.653.5822

- 1. James Hardie will only ship HardieReveal2.0™ Panel with HardieReveal2.0 Trims Full Pallet, Sub Pallet and Carton QTYs only
- 2. All HardieReveal2.0 Panel projects will be quoted as a lump sum project price
- 3. Quote applies only to the parties listed on this document
- 4. Quotes expire (90) days after date on quote
- 5. Pricing is locked for one year (365 days) from the date of the contract

•	ulti-Family orders	ys) from the date of the contract	'		
	SKU	Description	Qty	Unit	Tota
AB	9000324	COUNTERSUNK FILLER Reveal 2.0 Filler usage rate for countersunk fastening application, 1 box of filler per 1 pallet (40 sheets) of HardieReveal2.0 panels	1	Вох	
	9000405	EDGE SEALER (4 OZ. BOTTLE) - Conservative usage rate is two 4 oz. bottles of edge sealer for every 40 Panels	1	Bottle	
	9000322 (Drill Bit) 9000323 (Collar)	HARDIEREVEAL2.0 CS Bit Usage rate for countersunk fastening application, 1 unit per 1 pallet (40 sheets) of HardieReveal2.0 panels	1	Unit	
	9000315	HARDIEREVEAL2.0 COUNTERSUNK FASTENER WOOD	1,000	Вох	
	9000316	HARDIEREVEAL2.0 COUNTERSUNK FASTENER STEEL	1,000	Вох	
• (====================================	9000403 (Wood & Steel)	HARDIEREVEAL2.0 EXPOSED FASTENERS	250	Вох	
		PRESSURE TREATED PLYWOOD FURRING (MCA & MCQ TREATED LUMBER) Minimum 3/4 in. thick by 2 in. wide; 8 ft. or 10 ft. long pieces recommended	Not supplied by James Hardie		
		EPDM Minimum 1/16 in. thick EPDM to be installed on face of furring	Not supplied by James Hardie		
		PAINTING DO NOT use stain on James Hardie® products. James Hardie products must be painted within 180 days for primed product and 90 days for unprimed. Two coats of 100% acrylic topcoats with flat or satin sheen (20 or less gloss units at 60 degree angle) are recommended. Do not paint when wet. For application rates, refer to paint manufacturers specifications. Back-rolling is recommended if the product is sprayed. Please see Reveal 2.0 Filler Application Guide.	Not supplied by James Hardie		
		PANEL SAW WITH HARDIEBLADE® SAW BLADE	Not sup	plied by	

IN CONJUNCTION WITH HEPA VACUUM



James Hardie